## § 600.206-86

projections supplied in accordance with §600.208(a)(3).

- (ii) Within each group of data, all values are harmonically averaged and rounded to the nearest 0.0001 of a mile per gallon in order to determine FTP-based city and HFET-based highway fuel economy values for each subconfiguration at which the vehicle configuration was tested.
- (iii) All FTP-based city fuel economy values and all HFET-based highway fuel economy values calculated in paragraph (a)(2)(ii) of this section are (separately for city and highway) averaged in proportion to the sales fraction (rounded to the nearest 0.0001) within the vehicle configuration (as provided to the Administrator by the manufacturer) of vehicles of each tested subconfiguration. The resultant values, rounded to the nearest 0.0001 mile per gallon, are the FTP-based city and HFET-based highway fuel economy values for the vehicle configuration.
- (3) For the purpose of determining average fuel economy under §600.510–08, the combined fuel economy value for a vehicle configuration is calculated by harmonically averaging the FTP-based city and HFET-based highway fuel economy values, as determined in §600.206(a)(1) or (2) of this section, weighted 0.55 and 0.45 respectively, and rounded to the nearest 0.0001 mile per gallon. A sample of this calculation appears in Appendix II of this part.
- (4) For alcohol dual fuel automobiles and natural gas dual fuel automobiles the procedures of paragraphs (a)(1) or (2) of this section, as applicable, shall be used to calculate two separate sets of FTP-based city, HFET-based highway, and combined fuel economy values for each configuration.
- (i) Calculate the city, highway, and combined fuel economy values from the tests performed using gasoline or diesel test fuel.
- (ii) Calculate the city, highway, and combined fuel economy values from the tests performed using alcohol or natural gas test fuel.
- (b) If only one equivalent petroleumbased fuel economy value exists for an electric configuration, that value, rounded to the nearest tenth of a mile per gallon, will comprise the petro-

leum-based fuel economy for that configuration.

(c) If more than one equivalent petroleum-based fuel economy value exists for an electric vehicle configuration, all values for that vehicle configuration are harmonically averaged and rounded to the nearest 0.0001 mile per gallon for that configuration.

[71 FR 77944, Dec. 27, 2006]

## § 600.206-86 Calculation and use of fuel economy values for gasolinefueled, diesel, and electric vehicle configurations.

- (a) Fuel economy values determined for each vehicle, and as approved in §600.008 (b) or (f), are used to determine city, highway, and combined fuel economy values for each vehicle configuration (as determined by the Administrator) for which data are available.
- (1) If only one set of city and highway fuel economy values is accepted for a vehicle configuration, these values, rounded to the nearest tenth of a mile per gallon, comprise the city and highway fuel economy values for that configuration.
- (2) If more than one city or highway fuel economy value is accepted for a vehicle configuration:
- (i) All data shall be grouped according to the subconfiguration for which the data were generated using sales projections supplied in accordance with \$600.207(a)(3).
- (ii) Within each group of data, all values are harmonically averaged and rounded to the nearest 0.0001 of a mile per gallon in order to determine city and highway fuel economy values for each subconfiguration at which the vehicle configuration was tested.
- (iii) All city fuel economy values and all highway fuel economy values calculated in paragraph (a)(2)(ii) of this section are (separately for city and highway) averaged in proportion to the sales fraction (rounded to the nearest 0.0001) within the vehicle configuration (as provided to the Administrator by the manufacturer) of vehicles of each tested subconfiguration. The resultant values, rounded to the nearest 0.0001 mile per gallon, are the city and highway fuel economy values for the vehicle configuration.

## **Environmental Protection Agency**

- (3) The combined fuel economy value for a vehicle configuration is calculated by harmonically averaging the city and highway fuel economy values, as determined in §600.206(a) (1) or (2), weighted 0.55 and 0.45 respectively, and rounded to the nearest 0.0001 mile per gallon. A sample of this calculation appears in appendix II to this part.
- (b) If only one equivalent petroleumbased fuel economy value exists for an electric configuration, that value, rounded to the nearest tenth of a mile per gallon, will comprise the petroleum-based fuel economy for that configuration.
- (c) If more than one equivalent petroleum-based fuel economy value exists for an electric vehicle configuration, all values for that vehicle configuration are harmonically averaged and rounded to the nearest 0.0001 mile per gallon for that configuration.

[49 FR 13849, Apr. 6, 1984]

- § 600.206-93 Calculation and use of fuel economy values for gasolinefueled, diesel-fueled, electric, alcohol-fueled, natural gas-fueled, alcohol dual fuel, and natural gas dual fuel vehicle configurations.
- (a) Fuel economy values determined for each vehicle, and as approved in §600.008 (b) or (f), are used to determine city, highway, and combined fuel economy values for each vehicle configuration (as determined by the Administrator) for which data are available.
- (1) If only one set of city and highway fuel economy values is accepted for a vehicle configuration, these values, rounded to the nearest tenth of a mile per gallon, comprise the city and highway fuel economy values for that configuration.
- (2) If more than one city or highway fuel economy value is accepted for a vehicle configuration:
- (i) All data shall be grouped according to the subconfiguration for which the data were generated using sales projections supplied in accordance with \$600.207(a)(3).
- (ii) Within each group of data, all values are harmonically averaged and rounded to the nearest 0.0001 of a mile per gallon in order to determine city and highway fuel economy values for

each subconfiguration at which the vehicle configuration was tested.

- (iii) All city fuel economy values and all highway fuel economy values calculated in paragraph (a)(2)(ii) of this section are (separately for city and highway) averaged in proportion to the sales fraction (rounded to the nearest 0.0001) within the vehicle configuration (as provided to the Administrator by the manufacturer) of vehicles of each tested subconfiguration. The resultant values, rounded to the nearest 0.0001 mile per gallon, are the city and highway fuel economy values for the vehicle configuration.
- (3) The combined fuel economy value for a vehicle configuration is calculated by harmonically averaging the city and highway fuel economy values, as determined in §600.206(a) (1) or (2), weighted 0.55 and 0.45 respectively, and rounded to the nearest 0.0001 mile per gallon. A sample of this calculation appears in Appendix II to this part.
- (4) For alcohol dual fuel automobiles and natural gas dual fuel automobiles the procedures of paragraphs (a) (1) through (3) of this section shall be used to calculate two separate sets of city, highway, and combined fuel economy values for each configuration.
- (i) Calculate the city, highway, and combined fuel economy values from the tests performed using gasoline or diesel test fuel.
- (ii) Calculate the city, highway, and combined fuel economy values from the tests performed using alcohol or natural gas test fuel.
- (b) If only one equivalent petroleum-based fuel economy value exists for an electric configuration, that value, rounded to the nearest tenth of a mile per gallon, will compose the petroleum-based fuel economy for that configuration.
- (c) If more than one equivalent petroleum-based fuel economy value exists for an electric vehicle configuration, all values for that vehicle configuration are harmonically averaged and rounded to the nearest 0.0001 mile per gallon for that configuration.

[59 FR 39655, Aug. 3, 1994]